

MAINTENANCE INSTRUCTIONS FOR FINISHED WHITE INTERIOR PANEL

Handling

Our surface-treatment of the interior panel is done with water-based paints. This means a significantly reduced burden on both the internal and external environment, without our having to compromise on the panel's quality characteristics.

There are certain things that you must consider when it comes to water-based products. After painting and drying, the paint needs about two to four weeks to achieve maximum hardness and durability. Therefore, during this time, you should not expose surfaces to:

- Hard pressure stress
- Wear and tear
- Chemical effects
- Scratching with sharp or discolouring objects

Cleaning

Normal cleaning of lightly soiled surfaces is best performed with a damp soft cloth and a mild detergent such as dish-washing liquid or something similar. Do not use scouring powders or other agents that have an abrasive effect and do not use highly alkaline cleaners such as ammonia. Solvents such as thinners, denatured alcohol or similar cannot be used because they will dissolve the surface.

Maintenance

Do not allow dirt, stains, etc., remain too long on surfaces without regular cleaning, or whenever the need arises. In that way, you avoid having to expose surfaces for harder cleaning than necessary. Also, do not expose them to heat exposure and never let water stand.

If you follow the above instructions, you will have a durable paint surface for many years that is neither affected by light or darkness and which retains both colour and gloss.