

Declaration of performance

Declaration of performance number:
DoP01-2503-Sveden Trä

Product type unique identification code
Solid wood panelling and cladding with or without tongue

Intended use:
Internal and/or external finishes in solid wood panellings and cladding

Manufacturer
Company: Rågsveden – Sveden Trä AB
Address: Näset 117
S-786 94 Äppelbo, Sweden
Telefon: +46 10 471 91 00
Email: info@svedentra.se
Homepage: www.svedentra.se

System for assessment and continuous control of the performance of the construction product
System 4

Harmonized standard
EN 14915:2013


Solid wood panelling and cladding with or without tongue	
Essential characteristics	Performance
Species	Redwood (Pinus sylvestris) / Whitewood (Picea abies)
Density	Minimum mean density 390 kg/m ³
Reaction to fire	D-s2, d2, minimum thickness total 9 mm, minimum thickness 6 mm according to table 1. D-s2, d0, minimum thickness total 12 mm, minimum thickness 8 mm according to table 1. NOTE! This applies to panels without an air gap or with a closed air gap behind.
Natural biological durability (EN 350)	Class 4
Release of formaldehyde	E1
Content of pentachlorophenol	≤ 5 x 10 ⁻⁶ n
Water vapour permeability	50
Sound absorption coefficient	0,10/0,30
Thermal resistance	0,11 W/mK

This declaration of performance is issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Our construction product complies with the above stated performance.

Äppelbo 21 March 2025

Rågsveden – Sveden Trä AB


.....
(Signature)

Sven Brandt Coordinator